

A RECIPROCATING FLUID TRANSFER PUMP

BACKGROUND OF THE INVENTION

The present invention relates to an improvement in a reciprocating fluid transfer pump in which a fluid-in-transfer once having flown into a fluid delivering chamber is discharged therefrom by expanding and contracting a diaphragm disposed at an end portion of a center rod capable of making a reciprocating movement relative to a main body block and defining the fluid delivering chamber and a driving chamber.

In a reciprocating fluid transfer pump as described in US Patent No. 6,106,246, there has been used a diaphragm-type pump comprising a center rod capable of being driven to make a reciprocating motion relative to a main body block, in which a pair of diaphragms is secured to both ends of said center rod such that each of said pair of diaphragms may be located in place within head space so as to separate it to define a fluid delivering chamber and a driving chamber respectively, wherein when the center rod is to be driven toward one side, a driving fluid (e.g., a compressed air) is supplied into the driving chamber located in an other side, an opposite side of said one side, of the center rod so as to discharge a fluid-in-transfer in the fluid delivering chamber located in said other side, and at the same time, the fluid-in-transfer is suctioned into the fluid delivering chamber located in said one side of the center rod while allowing the driving fluid in the driving chamber located in said

one side to be exhausted, and when the center rod is to be driven toward said other side, the driving fluid is supplied into the driving chamber located in said one side of the center rod so as to discharge the fluid-in-transfer in the fluid delivering chamber located in said one side, and at the same time, the fluid-in-transfer is suctioned into the fluid delivering chamber located in said other side of the center rod while allowing the driving fluid in the driving chamber located in said other side to be exhausted, so that the fluid-in-transfer may be transferred continuously through this reciprocating motion of the center rod.

In this regard, said diaphragm-type pump comprises a pilot valve assembly block and a change-over valve assembly block, both of which are mounted on a main body block of the pump, said pilot valve assembly block including a pilot valve integrated therein as one body for detecting reciprocating strokes of the center rod and said change-over valve assembly block including a change-over valve integrated therein as one body for switching flow channels of the driving fluid based on a detection signal from the pilot valve.

However, in mounting operation of these valve assembly blocks, respective ports of the pilot valve assembly block must be positioned in proper locations with respect to respective ports of the change-over valve assembly block so as to form the flow channels for the driving fluid, and consequently this requires a certain

level of machining precision for positioning the pilot valve assembly block relative to the main body block as well as the assembling precision therebetween.

Some diaphragm-type pumping apparatuses have
5 employed an alternative configuration in which a positioning operation of the pilot valve assembly block relative to the main body block is not required in assembling therebetween but tubes for defining the flow channels are used so as to connect respective ports of the
10 change-over valve assembly block with respective ports of the pilot valve assembly block, but this type of pumping apparatus could also lead to such an unfavorable situation owing to the tubes being laid externally, that the tubes may cause an interference with other structures located in
15 the peripheral regions of the apparatus, and that in case of breakage or disconnection of the tube, the driving fluid could be leaked out.

This type of pumping apparatus is also suffered from another problem that since the position of respective
20 ports of the pilot valve assembly block is not fixedly defined relative to the respective ports of the change-over valve assembly block, the assembling location of the incorporated tubes is changed occasionally, which could make undesirable variation in performance of the diaphragm
25 pump.

The present invention has been made in the light of the circumstances as described above, and an object thereof is to provide a reciprocating fluid transfer pump

having such a configuration in which a pilot valve assembly block can be mounted to a main body block in a simple and easy manner without requiring particularly high level of machining precision for positioning the pilot valve assembly block relative to the main body block.

SUMMARY OF THE INVENTION

According to the present invention, there is provided a reciprocating fluid transfer pump in which a fluid-in-transfer once having suctioned into a fluid delivering chamber is discharged by expanding and contracting a barrier membrane or a diaphragm attached to an end portion of a center rod capable of making a reciprocating movement relative to a main body block and defining said fluid delivering chamber and a driving chamber, said reciprocating fluid transfer pump characterized in that a peripheral portion of said barrier membrane is clamped and thus secured to said main body block via a main ring and a sub ring, and a pilot valve assembly block having a pilot valve integrated therein as one body for detecting a reciprocating motion of said center rod is pressed against and thus secured to said main body block with the aid of said main ring and said sub ring.

According to one aspect of the present invention, there is provided a reciprocating fluid transfer pump in which a change-over valve assembly block having a change-over valve integrated therein as one body for switching movable directions of said center rod is secured fixedly

to said main body block, wherein said change-over valve assembly block and said pilot valve assembly block are interconnected via a piping block defining flow channels for connecting respective ports of said change-over valve with respective ports of said pilot valve.

According to another aspect of the present invention, there is provided a reciprocating fluid transfer pump in which said respective ports are connected to said respective flow channels of said piping block via connectors.

According to further aspect of the present invention, there is provided a reciprocating fluid transfer pump in which said piping block is secured fixedly to said main body block via said pilot valve assembly block.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a sectional view of a diaphragm pump according to an embodiment of the present invention taken along the line A-A of Fig. 2;

Fig. 2 is a sectional view of the diaphragm pump according to the embodiment of the present invention taken along the line B-B of Fig. 3;

Fig. 3 is a front elevational view, partly in cross section, of the diaphragm pump according to the embodiment of the present invention;

Fig. 4 is a side elevational view of the diaphragm pump according to the embodiment of the present invention, viewed from the direction indicated by the arrow X in Fig. 3;

Fig. 5 is a fragmentary view of Fig. 4 partly in section within areas of a piping block; and

Fig. 6 is a schematic diagram conceptually illustrating an operation of a diaphragm pump according to the embodiment of the present invention, wherein (A) shows a mode in which a center rod is moving toward one direction and (B) shows another mode in which the center rod is moving toward the other direction;

wherein, reference numeral 2 designates a main body block; 5 a center rod; 6 and 7 barrier membranes (diaphragms); 16 a pilot valve; 17 and 18 pilot valve assembly blocks; 19 and 20 fluid delivering chambers; 21 and 22 driving chambers; 26 a piping block; 30 a main ring; and 34 a sub ring.

DETAILED DESCRIPTION OF THE INVENTION

In Fig. 3, reference numeral 1 designates a base plate and 2 designates a main body block. The main body block 2 is secured to the base plate 1 in any appropriate manner and is provided with, as shown in Fig. 2, a supply passage 3 for supplying a fluid-in-transfer and a discharge passage 4 for discharging said fluid-in-transfer, each formed therein, and also a center rod 5 incorporated therein, as shown in Fig. 1, so as to be capable of making a reciprocating motion.

To respective opposite ends of the center rod 5 are attached diaphragms 6 and 7, which are exemplary embodiments of the barrier membranes. In this case, a peripheral portion 6a, 7a of the diaphragm 6, 7 is clamped

by a main ring 30 and a main body block 2, which will be described later in detail.

In the main body block 2, an intake port 8, 9 is arranged in a supply passage 3 and a discharge port 10, 11 is arranged in the discharge passage 4. The intake ports 8 and 9 and the discharge ports 10 and 11 are provided with ball valves 12-15 functioning as check valves for opening and closing those respective ports.

A pilot valve assembly 17, 18 having a pilot valve 16 integrated therein as one body is disposed in each side of the main body block 2. A configuration and function of the pilot valve 16 are well known and their detailed description will be herein omitted.

A space between this pilot valve assembly block 17, 18 and the main body block 2 is partitioned into a fluid delivering chamber 19, 20 and a driving chamber 21, 22 by the diaphragms 6, 7, wherein the pilot valve assembly block 17, 18 is also used as the driving chamber defining block. The supply passage 3 is in communication with the fluid delivering chamber 19, 20 via the intake port 8, 9, and the fluid delivering chamber 19, 20 is in turn communicating with the discharge passage 4 via the discharge port 10, 11.

In the main body block 2, a change-over valve assembly block 23 is secured thereto via a bolt 23A as shown in Fig. 2, and this change-over valve assembly block 23 includes a change-over valve 24 for switching the movable directions of the center rod 5 as well as an

exhaust valve element 25, both of which are integrated therein as one body. Configurations and functions of the change-over valve 24 and the exhaust valve element 25 are well known and their detailed description will be herein
5 omitted.

Each port 24a of the change-over valve 24 and each port 16a of the pilot valve 16 are interconnected via a connector 27 of a piping block 26 to form a flow channel 26a. The piping block 26 is secured to the pilot valve
10 assembly block 17, 18 by a bolt 28 as shown in Fig. 4 and Fig. 5.

The main ring 30 comprises, as shown in Fig. 1, an outer peripheral annular portion 31 and an inner peripheral annular portion 32, which together define an annular space into which an annular wall 33 formed in the
15 main body block section 2 is to be inserted. An annular threaded section 33a is formed on the outer surface of the annular wall 33 and an annular threaded section 31a is formed on the inner surface of the outer peripheral
20 annular portion 31.

The inner peripheral annular portion 32 has a clamping end portion 32a which cooperates with the main body block 2 to clamp the diaphragm 6, 7 in the peripheral portion thereof and also has an internal flange 32b
25 projecting radially toward the inner direction.

When the main ring 30 is engaged via thread and thus attached with the main body block 2, the pilot valve assembly block 17, 18 is pressed against the main body

block 2 so as not to drop out from the connection with the main body block 2 by the aid of the main ring 30, but the pilot valve assembly block 17, 18 is free to move rotationally until it is fastened tightly by the sub ring 34, which will be described later.

An annular threaded section 17a, 18a is formed on the outer surface of the pilot valve assembly block 17, 18. The annular threaded section 17a, 18a is to be engaged via thread with the sub ring 34 having an annular threaded section 34a in the inner surface thereof.

When the pilot valve assembly block 17, 18 is to be mounted to the main body block 2 such that each port 16a of the pilot valve 16 may be connected with each port 24a of the change-over valve 24 to form the flow channel 26a, firstly the connector 27 of the piping block 26 is coupled to each port 24a of the change-over valve 24; secondly the pilot valve assembly block 17, 18 is rotationally moved relative to the main body block 2 so as to connect each port 16a of the pilot valve 16 to the connector 27 of the piping block 26; thirdly the sub ring 34 is turned toward the direction for engaging itself via thread with and thus being fastened to the threaded section of the pilot valve assembly block 17, 18; and thereby the pilot valve assembly block 17, 18 comes into contact with the internal flange 32b. Through these operations, the pilot valve assembly block 17, 18 together with the diaphragm 6, 7 is fixedly secured with the aid of main ring 30 and the sub ring 34. After that, the piping block 26 is fastened and

secured to the pilot valve assembly block 17, 18 via a bolt 28.

In the diaphragm-type pump provided as an exemplary embodiment of the reciprocating fluid transfer pump having the above-described configuration, when a compressed air is supplied into the driving chamber 22 located in the right hand side (the other side), then the center rod 5 is moved toward the left hand side (the one side) as shown in Fig. 6(A), and the expanding and contracting action of the diaphragm 7 pushes out a fluid-in-transfer in the fluid delivering chamber 20 located in the right hand side (the other side) to flow into the discharge passage 4. At the same time with this, the compressed air in the driving chamber 21 in the left hand side (the one side) is exhausted to the outside, while simultaneously the fluid-in-transfer is suctioned into the fluid delivering chamber 19 in the left hand side (the one side) through the supply passage 3. When the pilot valve 16 detects the contact of the center rod 5, the change-over valve 24 changes over the flow channels 26a automatically so as for the center rod 5 to be moved toward the right hand side (the other side) as shown in Fig. 6(B), where the expanding and contracting action of the diaphragm causes the compressed air to be supplied into the driving chamber 21 located in the left hand side (the one side) and the fluid-in-transfer in the fluid delivering chamber 19 in the left hand side (the one side) to be pushed out to flow into the discharge passage 4. At the same time with this, the

compressed air in the driving chamber 22 in the right hand side (the other side) is exhausted to the outside, while simultaneously the fluid-in-transfer is supplied into the fluid delivering chamber 20 in the right hand side (the
5 other side) through the supply passage 3.

It is to be noted that in Fig. 1, each of reference numerals 35 and 36 designates an O-ring for blocking any leakage from the fluid delivering chamber 19, and reference numeral 37 designates an compressed air release
10 plug.

According to the present invention, because of the configuration as described above, the barrier membrane implemented by, for example, the diaphragm can be mounted between the main body block and the pilot valve assembly
15 block in a simple and easy manner as well as in finely sealed condition without requiring particularly high level of machining precision for positioning the pilot valve assembly block relative to the main body block.